




**COOL SOLUTIONS
FOR PROFESSIONALS**



Tubs 360x165



Tubs 360x250



TECHNICAL DATA	AGF0062
Nominal Depth mm	870
Capacity L.	590
Dimensions WxDxH	700x870x2080
Light door WxH	550x1480
Inner depth	725
Depth with 90° door	1490
Climatic class	T
Operating temperature °C	-30/-5
Refrigerant	R404
Refrigeration capacity W	572* 848**
Electric power supply V/~/Hz	230/1/50
Max. power W	820
Max. absorbed current A	4,4
Refrigeration system	VENTILATED AIR FORCED
Internal fittings shelves	5 x (500x700)
Interstep	35 - 50
Standing	36—25
Packing dimensions	740x890x2200
Packing volume	1,45
Net weight kg	135
Gross weight kg	150
(*) Temp.evap. -10°C, Temp. cond. +45°C	
(**) Temp.evap. +7,2°C, Temp.cond. +54.4°C	

AGF0062

HIGH-END FREEZER FOR GELATO

Up to **48 tubs** 360x165x120

Up to **32 tubs** 360x250x120

AGF0062 AIR

STANDARD EQUIPPED WITH 5 STAINLESS STEEL SHELVES
500X700 AND 5 PAIR OF STAINLESS STEEL RUNNERS

Extra pair "C" runners	FPCG57I
Extra stainless steel shelves	RFI57P
Castors kit	BN219901

GENERAL FEATURES

- Stainless steel framework construction, monocoque structure
- Scotch brite external finish
- **75 mm insulation** (high density 40 Kg/mc, CFC and HCFC free)
- Door frame with replaceable electric resistance
- Magnetic gaskets replaceable without tools
- **Automatic self-closing REVERSIBLE door**
- **Compensation valve** to ease door openings
- Front hinges for installation on concrete plinths
- Adjustable stainless steel feet
- **Rounded corners** for better cleaning
- Stainless steel tray supports with pierced diamond pattern to adjust trays' height every 3,5 or 5 cm (standings nr. 36 - 25)

REFRIGERANT UNIT

- **Indirect ventilated** air circulation system (**on sides**) with flow conveyor to ensure temperature uniformity and perfect product preservation
- **Autom ventilation stop** when opening doors, controlled by micro-switch
- Intelligent defrosting: only when needed, electric
- **MONOBLOCK** cooling system: all in one block above the cabinet
- Quick temperature recovery (to compensate with frequent door openings)
- Evaporator with anticorrosion **cataphoresis** treatment, with capillar
- Control board with "**LAB**" function (continuous freezing)

COMMANDS, CONTROLS AND SAFETY DEVICES

- electronic control board

OPTIONS / ACCESSORIES

- Castors available on request
- Available with water cooled unit
- Additional runners and stainless steel shelves